


MULTIMAX MP 522

TIRE SIZE	440/80 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	161 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94052257	RC (IN)	155.8
SW (IN)	17.4	RIM REC	DW 14 L
OD (IN)	51.7	RIM ALT	DW 13; DW 13 L; DW 15 L
SLR (IN)	23.1	ECE	E11-106R-002966

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	4890	5820	6640	7550	8470	9080	10200	-	-
25	4890	5820	6640	7550	8470	9080	10200	-	-
20	5250	6230	7100	8080	9060	9720	10910	-	-
15	5430	6460	7360	8380	9400	10090	11320	-	-
5 CYC.	5970	7350	8650	9950	11330	12320	13930	14690	15300
STATIC	9150	11260	13260	15260	17360	18890	21350	22520	23460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.