


AGRIMAX RT 657

TIRE SIZE	650/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDIMIADORA / TRACTOR / COSECHADORA
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	163 D ; 166 A8



DIMENSIONES US STANDARD

CÓDIGO USA	94076260	RC (IN)	215.9
SW (IN)	25.4	RIM REC	DW 20 B
OD (IN)	71.3	RIM ALT	DW 21 B ; DW 23 B
SLR (IN)	32.7	ECE	E4-106R-000624

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	5160	6020	6780	7530	8280	8930	9890	10700
30	5420	6330	7120	7900	8700	9370	10390	11290
25	5610	6550	7360	8180	9010	9700	10760	11680
20	5940	6930	7790	8660	9520	10270	11390	12370
5 LT	6920	8070	9080	10090	11100	11960	13260	14410
5 HT	5940	6930	7790	8660	9520	10270	11390	12370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.