DATA SHEET

PRINTED ON
21-04-2026

AS 504

TIRE SIZE	**425/50 - 18**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	140 A8
LI/SS FREE ROLLING	152 A8

DIMENSIONS US STANDARD

USA CODE	94060092	**RC (IN)**	103.2
SW (IN)	16.1	**RIM REC**	14
OD (IN)	34.7	**RIM ALT**	13
SLR (IN)	16.1		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	10960
15 FR	9300
20 FR	8760
25 FR	7850
5 DW	7700
15 DW	6560
20 DW	6180
25 DW	5520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..