

DESERT KING



DESERT KING



DESERT KING is best suited for loose soil, sandy terrain and paver applications with desert trucks. The optimized rib tread design offers excellent flotation and directional stability. Its strong nylon casing and heavy-duty bead are specially developed for low pressure operations. DESERT KING provides also high punctures resistance and a longer tire life.



SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
Ø25"	29.5 - 25 DT	TL	E7	28	-	25.00/3.5	-	0	1822	786	5392	20,5	STD
	18.00 - 25 DT	TL	E7	16	-	10.00/1.5	-	0	1535	635	4405	16	STD
	21.00 - 25 DT	TL	E7	16	-	15.00/3.0	-	0	1660	708	4906	17,5	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
	 E7		
			
-	-		

Permissible tolerances: O.O. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index