

# AGRIMAX RT 855

|           |                                                                                 |
|-----------|---------------------------------------------------------------------------------|
| TIRE SIZE | 480/80 R 38                                                                     |
| UM        | IS STANDARD                                                                     |
| MACHINERY | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| VERSIÓN   | STANDARD                                                                        |
| TIRE TYPE | TL                                                                              |
| LI/SS     | 149 A8/B                                                                        |

## DIMENSIONES IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 475  | RIM REC | DW 16 L         |
| OD (MM)  | 1747 | RIM ALT | W 14 L ; W 15 L |
| SLR (MM) | 785  | ECE     | E4-106R-001822  |
| RC (MM)  | 5161 | SRI     | 825             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 40         | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 30         | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |
| 10 LT      | 2400 | 2790 | 3180 | 3575 | 3965 | 4355 |
| 10 HT      | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

