


# AGRIMAX SIRIO

<b>TIRE SIZE</b>	<b>540/65 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	HIGH SPEED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D ; 147 E



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1464	<b>RIM ALT</b>	W 18
<b>SLR (MM)</b>	669	<b>ECE</b>	E4-106R-000814
<b>RC (MM)</b>	4400	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1450	1665	1910	2155	2400	2645	2860	3075
65	1575	1810	2080	2345	2615	2885	3120	3350
50	1655	1905	2185	2465	3750	3030	3275	3520
40	1725	1985	2280	2570	2865	3160	3415	3670
25	1870	2145	2465	2780	3100	3415	3695	3970
10	2365	2715	3120	3520	3920	4325	4675	5025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.