


# RIDEMAX FROST

<b>TIRE SIZE</b>	<b>540/80 R 38 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	172 A8 ; 167 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94076604	<b>RC (IN)</b>	220.1
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	DW 18 L
<b>OD (IN)</b>	72.2	<b>RIM ALT</b>	DW 16 L
<b>SLR (IN)</b>	33.1	<b>ECE</b>	E11-106R-0010575

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	38	41	44	46
45	5290	6980	8410	9260	9850	10340	10810	11420	12010
30	5720	7540	9090	10010	10650	11180	11690	12350	12980
25	6120	8060	9720	10700	11400	11950	12500	13190	13890
20	6350	8370	10100	11110	11830	12400	12980	13700	14420
10	6670	8780	10600	11660	12420	13030	13630	14400	15140
5	7620	10040	12110	13330	14200	14890	15570	16450	17310
3	8840	11650	14050	15460	16470	17270	18070	19070	20070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.