


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 900/50 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94058471	<b>RC (IN)</b>	229.5
<b>SW (IN)</b>	34.7	<b>RIM REC</b>	DW 30 B
<b>OD (IN)</b>	77.0	<b>RIM ALT</b>	TW 30 B
<b>SLR (IN)</b>	34.3	<b>ECE</b>	E11-106R-006492

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7370	8500	9790	10910	12190	13320	14920	16050
<b>FROM 40 TO 25</b>	8110	9350	10760	11990	13400	14640	16400	17600
20	8430	9710	11190	12470	13930	15220	17050	18340
12	8750	10090	11620	12950	14470	15810	17710	19050
5	10300	13080	13660	15220	17020	18580	20820	22400
<b>UPTO 20 CYC</b>	10540	12150	13980	15590	17420	19020	21320	22930
<b>UPTO 10 CYC</b>	12570	14480	16670	18580	20770	22680	25420	27340
<b>UPTO 5 CYC</b>	13790	15880	18290	20380	22780	24880	27880	29980
5HT	8430	9710	11190	12470	13930	15220	17050	18340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.