


AGRIMAX RT 765M

TIRE SIZE	710/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	173 D ; 176 A8



DIMENSIONS US STANDARD

USA CODE	94066476	RC (IN)	243.1
SW (IN)	28.2	RIM REC	DW 23 B
OD (IN)	81.1	RIM ALT	DW 25 B
SLR (IN)	36.3	ECE	E11-106R-006018

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	6730	7740	8880	10030	11180	12320	13470	14330
30	7080	8130	9340	10540	11740	12940	14150	15050
25	7390	8480	9730	10990	12250	13500	14760	15700
15	7750	8910	10220	11540	12860	14170	15500	16480
5 LT	9030	10370	11920	13450	14980	16520	18050	19200
5 HT	7750	8910	10220	11540	12860	14170	15500	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.