


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	174 D



DIMENSIONS US STANDARD

CODE USA	94514168	RC (IN)	239.8
SW (IN)	28.1	RIM REC	DW 25 B
OD (IN)	80.4	RIM ALT	DW 27 B
SLR (IN)	35.3	ECE	E11-106R-0010941

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	7400	8610	9820	11030	12250	13450
FROM 40 TO 25	8120	9460	10790	12110	13450	14770
20	8290	9640	11000	12360	13710	15070
12	8450	9840	11220	12610	13990	15370
5	8940	10410	11870	13330	14790	16250
*UPTO 5 CYC WITH FRONT LOADER	11380	13240	15100	16960	18830	20680
5 HT	8290	9640	11000	12360	13710	15070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.