

# AW 702

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>13.0/55 - 16</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | BALER / IMPLEMENT MACHINERY / TRAILER / HARVESTER / IMPLEMENTS / TRAILER |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 130 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 336  | <b>RIM REC</b> | 11.0           |
| <b>OD (MM)</b>  | 770  | <b>ECE</b>     | E4-106R-001898 |
| <b>SLR (MM)</b> | 345  | <b>PR</b>      | 12             |
| <b>RC (MM)</b>  | 2256 |                |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.60 |
|------------|------|
| 10 FR      | 2660 |
| 25 FR      | 2260 |
| 30 FR      | 2130 |
| 40 FR      | 1900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.