

# TR 678 IND

<b>TIRE SIZE</b>	<b>600/40 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ЭКСКАВАТОР
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	157 A8
<b>LI/SS FREE ROLLING</b>	169 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	615	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1085	<b>ECE</b>	E11-106R-006973
<b>SLR (MM)</b>	483		
<b>RC (MM)</b>	3264		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>4.10</b>
<b>40 FR</b>	5800
<b>40 DW</b>	4125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.