


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>750/65 R 26</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94064311	<b>RC (IN)</b>	196.3
<b>SW (IN)</b>	29.5	<b>RIM REC</b>	DW 24 B
<b>OD (IN)</b>	64.4	<b>RIM ALT</b>	DW 23 B ; DW 25 B
<b>SLR (IN)</b>	29.0	<b>ECE</b>	E11-106R-006182

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	29	35	41	46	49	55
30	6240	7190	8130	8820	9630	10710	11530	12610	13560	-	-
25	6240	7190	8130	8820	9630	10710	11530	12610	13560	-	-
20	6680	7700	8720	9450	10320	11470	12350	13500	14520	-	-
5 LT	8370	9630	10910	11820	12910	14360	15450	16910	18180	-	-
5 HT	6680	7700	8720	9450	10320	11470	12350	13500	14520	-	-
5 CYC	-	11550	13070	14160	15460	17220	18520	20260	21780	22130	23050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.