

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>480/70 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDEMMIATRICE / MACCHINA PER IL RACCOLTO DI FRUTTETI / TRATTORINO / TRATTORE / MIETITREBBIA
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	141 A8 ; 141 B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1478	<b>RIM ALT</b>	W 14 L ; W 16 L
<b>SLR (MM)</b>	660	<b>ECE</b>	E11-106R-009050
<b>RC (MM)</b>	4396	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1420	1650	1880	2115	2345	2575
40	1420	1650	1880	2115	2345	2575
30	1520	1770	2015	2265	2515	2760
10 LT	1905	2215	2525	2835	3145	3455
10 HT	1520	1770	2015	2265	2515	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.