


# AGRIMAX RT 855

<b>TYRE SIZE</b>	<b>520/85 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	158 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94030569	<b>RC (IN)</b>	242.4
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L; W 16 A; W 16 L; DD 16
<b>OD (IN)</b>	80.8	<b>RIM ALT</b>	DW 18 L; W 18 L; W 18 A
<b>SLR (IN)</b>	36.6	<b>ECE</b>	E4-106R-001415

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
30	5160	6000	6840	7680	8530	9370
25	5160	6000	6840	7680	8530	9370
20	5520	6430	7330	8230	9140	10030
5 LT	6910	8040	9170	10300	11430	12550
5 HT	5520	6430	7330	8230	9140	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.