


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 D ; 181 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	706	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1959	<b>RIM ALT</b>	DW 25 B
<b>SLR (MM)</b>	881	<b>ECE</b>	E11-106R-006178
<b>RC (MM)</b>	5926	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	2925	3450	3975	4425	4950	5400	5925	6375	6975	7500
50	3075	3625	4175	4650	5200	5670	6225	6695	7325	7875
40	3220	3795	4375	4870	5445	5940	6520	7015	7675	8250
30	3365	3970	4575	5090	5695	6210	6815	7335	8025	8625
10 LT	3920	4625	5330	5930	6635	7240	7940	8545	9350	10050
10 HT	3365	3970	4575	5090	5695	6210	6815	7335	8025	8625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.