


# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>340/80 R 18 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	143 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94048694	<b>RC (IN)</b>	119.2
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	11; 11 SDC; W 11
<b>OD (IN)</b>	39.4	<b>RIM ALT</b>	W 10; 12; 12 SDC
<b>SLR (IN)</b>	17.9	<b>ECE</b>	E4-106R-002981

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2890	3430	3910	4450	4990	5360	6010	-	-
25	2890	3430	3910	4450	4990	5360	6010	-	-
20	3100	3670	4190	4770	5350	5730	6440	-	-
15	3210	3800	4340	4940	5540	5940	6670	-	-
5 CYC.	3530	4330	5100	5860	6680	7260	8210	8660	9020
STATIC	5400	6640	7810	8990	10230	11130	12590	13270	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.