


RIDEMAX FL 615

TIRE SIZE	VF 800/65 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	REMORCĂ / CISTERNĂ / MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINI DE IMPLEMENTARE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	190 D



DIMENSIUNI US STANDARD

USA CODE	94513925	RC (IN)	220.9
SW (IN)	32.1	RIM REC	DW 28 B
OD (IN)	72.8	RIM ALT	DW 27 B
SLR (IN)	31.9	ECE	E11-106R-0010408

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41
40	11450	12850	15660	17770	20570	23370
30	13400	15050	18330	20790	24070	27350
25	14780	16590	20200	22920	26530	30150
20	16160	18130	22090	25050	29010	32960
15	16730	18770	22870	25940	30040	34130
10	17420	19540	23810	27010	31270	35530
5	18780	21090	25680	29130	33730	38330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.