


# RIDEMAX FL 693 M

<b>TIRE SIZE</b>	<b>VF 400/45 R 17.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94069323	<b>RC (IN)</b>	96.4
<b>SW (IN)</b>	15.7	<b>RIM REC</b>	14.00
<b>OD (IN)</b>	31.5	<b>ECE</b>	E11-106R-007199
<b>SLR (IN)</b>	14.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
45	2290	2780	3100	3570	4060	4420	4850	5320
40	2510	3040	3390	3920	4440	4850	5320	5840
30	3050	3680	4110	4750	5380	5870	6450	7080
25	3430	4130	4620	5330	6040	6600	7240	7950
20	3800	4600	5130	5920	6710	7330	8040	8830
15	3980	4810	5370	6190	7020	7670	8410	9240
5	4530	5480	6110	7050	8000	8730	9580	10520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.