

# AW 708

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	140 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94010363	<b>RC (IN)</b>	108.3
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	37.2	<b>ECE</b>	E4-106R-001884
<b>SLR (IN)</b>	16.4	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29
5 FR	7720
15 FR	6560
20 FR	6170
25 FR	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.