

# POWERTRAILER SR 331

<b>TIRE SIZE</b>	560/60 R 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / АВТОЦИСТЕРНА
<b>VERSION</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94073962	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	49.0	<b>RIM ALT</b>	17.00; AG18.00
<b>SLR (IN)</b>	22.2	<b>ECE</b>	E11-106R-0010087
<b>RC (IN)</b>	148.6		

## LOAD CAPACITY (LBS/TIRE)

MPH/PSI	46	52	58	65	73
5	15120	16550	18200	19420	20440
15	13270	14530	15970	17050	17930
25	11420	12500	13750	14670	15440
30	10160	11120	12240	13060	13730
40	8400	9190	10110	10790	11350
43	7640	8370	9190	9820	10330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.