


MULTIMAX MP 522

TIRE SIZE	440/80 R 28 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	156 A8/B



DIMENSIONS IS STANDARD

SW (MM)	441	RIM REC	DW 14 L
OD (MM)	1415	RIM ALT	DW 13 ; DW 13 L ; DW 15 L
SLR (MM)	643	ECE	E11-106R-002968
RC (MM)	4278	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2300	2725	2940	3150	3360	3575	3790	4000	-	-
40	2300	2725	2940	3150	3360	3575	3790	4000	-	-
30	2480	2930	3155	3380	3605	3830	4055	4280	-	-
25	2570	3040	3270	3505	3740	3970	4205	4440	-	-
10 CYC.	2840	3470	3790	4105	4420	4735	5050	5370	5685	6000
STATIC	4360	5330	5810	6295	6780	7265	7750	8230	8715	9200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.