


AGRIMAX RT 600

	1050/50 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	184 A8 ; 181 B



UNDEFINED US STANDARD

USA CODE	94040728	RC (IN)	224.4
SW (IN)	41.7	RIM REC	36.0 VA (multi-piece)
OD (IN)	73.3	ECE	E4-106R-000813
SLR (IN)	32.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	8190	9280	11640	12920	14370	15460	16920	18190	-	-
25	8930	10120	12700	14090	15670	16860	18450	19840	-	-
20	9560	10840	13590	15080	16780	18050	19750	21230	-	-
5 LT	11970	13570	17020	18880	21010	22610	24730	26590	-	-
5 HT	9560	10840	13590	15080	16780	18050	19750	21230	-	-
5 CYC	-	15010	19230	21090	24460	25470	27880	29970	31290	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.