

## TR 135

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>23.1 - 26</b>                                                                       |
| <b>UM</b>           | US STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRAKTOR / SLÄPVAGN                                                                     |
| <b>VERSION</b>      | DUAL BEAD                                                                              |
| <b>TIRE TYPE</b>    | TT                                                                                     |
| <b>LI/SS</b>        | 149 A8                                                                                 |



### DIMENSIONER US STANDARD

|                 |          |                |                   |
|-----------------|----------|----------------|-------------------|
| <b>USA CODE</b> | 94048014 | <b>RC (IN)</b> | 181.7             |
| <b>SW (IN)</b>  | 23.1     | <b>RIM REC</b> | DW 20 B ; DW 20 A |
| <b>OD (IN)</b>  | 62.4     | <b>ECE</b>     | E11-106R-004595   |
| <b>SLR (IN)</b> | 27.6     | <b>PR</b>      | 12                |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>24</b> |
| 25               | 7150      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.