DATA SHEET

PRINTED ON
22-04-2026

AS 504

TIRE SIZE	**10.0/75 - 15.3**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	111 A8
LI/SS FREE ROLLING	123 A8

ABMESSUNGEN US STANDARD

USA-CODE	94018567	**RC (IN)**	94.6
SW (IN)	10.4	**RIM REC**	9.00
OD (IN)	30.9	**ECE**	E4-106R-001812
SLR (IN)	14.2	**PR**	10

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	57
5 FR	4780
15 FR	4070
20 FR	3820
25 FR	3420
5 DW	3360
15 DW	2850
20 DW	2690
25 DW	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..