

# AS 2001

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | <b>16.9 - 28</b> |
| <b>UM</b>           | US STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | TRACTOR          |
| <b>VERSION</b>      | SPECIAL          |
| <b>TIRE TYPE</b>    | TT               |
| <b>LI/SS</b>        | 139 A8           |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94002825 | <b>RC (IN)</b> | 170.0           |
| <b>SW (IN)</b>  | 16.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>  | 55.9     | <b>RIM ALT</b> | W 14 L          |
| <b>SLR (IN)</b> | 25.6     | <b>ECE</b>     | E11-106R-004345 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>36</b> |
| 25               | 5360      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.