

# BK 826

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>8.25 - 16</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | ПРИЦЕП /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / КОМБАЙН /<br>ПРИЦЕП / ЭКСКАВАТОР-<br>ПОГРУЗЧИК |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## РАЗМЕРЫ IS STANDARD

|                |        |            |                |
|----------------|--------|------------|----------------|
| <b>SW (MM)</b> | 238    | <b>ECE</b> | E4-54R-0024096 |
| <b>OD (MM)</b> | 863    | <b>PR</b>  | 16             |
| <b>RIM REC</b> | 6.50 H |            |                |
| <b>RIM ALT</b> | 6.00 G |            |                |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.60</b> |
| <b>100 LS</b>     | 1850        |
| <b>100 LD</b>     | 1750        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.