


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	2019	<b>RIM ALT</b>	DW 25 B
<b>SLR (MM)</b>	915	<b>ECE</b>	E11-106R-004896
<b>RC (MM)</b>	6103	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
<b>50</b>	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
<b>40</b>	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
<b>30</b>	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025
<b>10 LT</b>	3720	4325	4925	5630	6235	6835	7540	7940	8745	9450	10050
<b>10 HT</b>	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.