


RIDEMAX FL 693 M



560/55 R 22.5

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / RÖMÖRK / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	162 D

UNDEFINED IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1180	RIM ALT	17.00; 20.00
SLR (MM)	533	ECE	E11-106R-006972
RC (MM)	3614	SRI	550

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
70	1645	1990	2205	2555	2900	3200	3505	3850	4110	4325
65	1805	2185	2425	2805	3185	3515	3850	4230	4515	5750
50	2185	2645	2935	3395	3855	4255	4660	5120	5465	5750
40	2455	2975	3295	3815	4330	4785	5235	5750	6140	6460
25	2855	3455	3830	4430	5030	5555	6080	6680	7130	7505
10	3250	3935	4365	5045	5730	6330	6930	7610	8125	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.