


AT 171

| | |
|---------------------|--|
| TIRE SIZE | 40X10 - 22 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ВЕЗДЕХОД / ТРАКТОР ДЛЯ ЕЗДЫ ПО ГРЯЗИ / ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS | 95 A8 ; 71 F |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|-----------------|------|
| SW (MM) | 235 | RIM REC | W 8 |
| OD (MM) | 1005 | RIM ALT | W 7 |
| SLR (MM) | 469 | PR | 8 |
| RC (MM) | 2955 | TRA CODE | R1W+ |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.40 | 1.00 |
|---------------------|------|------|
| 40 MUD BOGGING | 690 | - |
| 80 MUD BOGGING | 345 | - |
| 40 CASUAL TRANSPORT | - | 565 |
| 80 CASUAL TRANSPORT | - | 285 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.