


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>540/80 R 38 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	172 A8 ; 167 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94055838	<b>RC (IN)</b>	218.0
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	W 18 L
<b>OD (IN)</b>	72.0	<b>RIM ALT</b>	W 16 L
<b>SLR (IN)</b>	32.8	<b>ECE</b>	E11-106R-004077

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	5640	6970	8170	9490	10690	12010
30	6110	7530	8830	10260	11550	12980
25	6530	8060	9450	10970	12360	13890
20	7840	9670	11330	13160	14840	16670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.