

# SL 441

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>200/60 - 14.5</b>                                  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | OUTILLAGE AGRICOLE / REMORQUE /<br>OUTILLAGE AGRICOLE |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS FREE ROLLING</b> | 113 A8  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94011094 | <b>RC (IN)</b> | 70.3            |
| <b>SW (IN)</b>  | 8.3      | <b>RIM REC</b> | AG 6.75         |
| <b>OD (IN)</b>  | 24.0     | <b>ECE</b>     | E11-106R-003610 |
| <b>SLR (IN)</b> | 10.9     | <b>PR</b>      | 14              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 102  |
|-----------|------|
| 5 FR      | 3550 |
| 15 FR     | 3020 |
| 20 FR     | 2840 |
| 25 FR     | 2540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.