


AGRIMAX SPARGO SB

| | |
|---------------------|--|
| TIRE SIZE | VF 270/95 R 48 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / FELDSPRITZE |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 155 D |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA-CODE | 94076499 | RC (IN) | 211.5 |
| SW (IN) | 11.0 | RIM REC | W9 |
| OD (IN) | 68.7 | ECE | E11-106R-0010463 |
| SLR (IN) | 32.1 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 14 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|---------------|------|------|------|------|------|------|------|------|------|------|
| 45 | 3660 | 4140 | 4600 | 4990 | 5540 | 5850 | 6390 | 6940 | 7400 | 7790 |
| FROM 40 TO 25 | 4030 | 4540 | 5050 | 5470 | 6080 | 6420 | 7020 | 7610 | 8130 | 8550 |
| 20 | 4110 | 4630 | 5150 | 5590 | 6200 | 6550 | 7160 | 7760 | 8290 | 8720 |
| 12 | 4180 | 4720 | 5250 | 5690 | 6320 | 6670 | 7290 | 7920 | 8450 | 8890 |
| 5 | 4430 | 5000 | 5560 | 6020 | 6680 | 7060 | 7720 | 8380 | 8940 | 9410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.