


# EARTHMAX SR 22 AS

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>23.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | LOADER / GRADER  |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 185 B ; 170 A8 ; 201 A2  |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94073405 | <b>RIM REC</b>     | 19.50/2.5 |
| <b>OD (IN)</b>  | 63.5     | <b>TRA CODE</b>    | E2/G2/L2  |
| <b>SLR (IN)</b> | 27.9     | <b>STAR RATING</b> | ★★/★/★★   |
| <b>RC (IN)</b>  | 191.5    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI        | 18        | 22   | 25   | 29   | 33    | 36    | 40    | 44    | 58    | 62    | 65    | 69    | 73    | 76    | 80    | 83    | 87    | 91    |
|------------------|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30               | -         | -    | -    | -    | -     | -     | -     | -     | 16500 | 17100 | 18200 | 18700 | 19800 | 20400 | -     | -     | -     | -     |
| 25               | 6950      | 7850 | 8800 | 9900 | 10700 | 11700 | 12300 | 13200 | -     | -     | -     | -     | -     | -     | -     | -     | -     | -     |
| 5                | -         | -    | -    | -    | -     | -     | -     | -     | -     | -     | -     | -     | -     | 27600 | 28300 | 29100 | 30000 | 30900 |
| <b>MPH / PSI</b> | <b>94</b> |      |      |      |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 30               | -         |      |      |      |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 25               | -         |      |      |      |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 5                | 32000     |      |      |      |       |       |       |       |       |       |       |       |       |       |       |       |       |       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.