

EARTHMAX SR 51



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 51

EARTHMAX SR 51 (L-5) is an All Steel radial tyre specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction. The extra deep tread ensures also great stability and an extended tyre life.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	20.5 R 25	TL	L5	*	186 A2	17.00/2.0	-	0	539	1545	703	4650	68	CR
	23.5 R 25	TL	L5	**	201 A2	19.50/2.5	-	0	612	1660	743	4882	77	CR
	17.5 R 25	TL	L5	*	176 A2	14.00/1.5	-	0	437	1398	630	4110	61	CR
	23.5 R 25	TL	L5	*	195 A2	19.50/2.5	-	0	612	1660	743	4882	77	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES	
				
				

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 15/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
	20.5 R 25	TL	L5	**	193 A2	17.00/2.0	-	-	539	1545	703	4650	68	CR
Ø29"	29.5 R 29	TL	L5	*	211 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	777	1990	842	5872	94	CR
	875/65 R 29 (35/65 R 29)	TL	L5	**	221 A2	27.00/3.5	27.00/3.0 28.00/3.5	0	878	1872	814	5616	92	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES	
				
	L5			
				
A2	221 kg			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 15/09/2026