

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>480/70 R 38</b>                                                              |
| <b>UM</b>        | US STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | SPECIAL                                                                         |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 145 D                                                                           |

## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94063208 | <b>RC (IN)</b> | 199.0           |
| <b>SW (IN)</b>    | 18.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>    | 66.2     | <b>RIM ALT</b> | W 14 L ; W 16 L |
| <b>SLR (IN)</b>   | 30.1     | <b>ECE</b>     | E11-106R-005832 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>40</b>   | 3520 | 4100 | 4670 | 5250 | 5820 | 6390 |
| <b>30</b>   | 3690 | 4300 | 4910 | 5510 | 6120 | 6710 |
| <b>25</b>   | 3860 | 4500 | 5130 | 5750 | 6380 | 7010 |
| <b>20</b>   | 4050 | 4710 | 5370 | 6030 | 6690 | 7350 |
| <b>5 LT</b> | 4720 | 5790 | 6260 | 7030 | 7800 | 8580 |
| <b>5 HT</b> | 4050 | 4710 | 5370 | 6030 | 6690 | 7350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

