


# MULTIMAX MP 529

<b>TIRE SIZE</b>	<b>400/70 R 20 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	415	<b>RIM REC</b>	13
<b>OD (MM)</b>	1090	<b>RIM ALT</b>	12 SDC;13SDC;14
<b>SLR (MM)</b>	500	<b>ECE</b>	E11-106R-0010769
<b>RC (MM)</b>	3314	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.2	4.4
50	1550	1825	2100	2375	2650	2950	3250	-	-
40	1550	1825	2100	2375	2650	2950	3250	-	-
30	1660	1960	2265	2570	2870	3175	3480	-	-
25	1730	2040	2355	2670	2980	3295	3610	-	-
10 CYC.	1910	2335	2760	3180	3605	4030	4455	4670	4880
STATIC	2930	3580	4230	4880	5530	6180	6830	7155	7480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.