

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	122 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	329	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1154	<b>RIM ALT</b>	W 9 ; W 10
<b>SLR (MM)</b>	519	<b>ECE</b>	E4-106R-000613
<b>RC (MM)</b>	3424	<b>SRI</b>	550

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	825	960	1095	1230	1365	1500
40	825	960	1095	1230	1365	1500
30	885	1030	1175	1320	1465	1605
10 LT	1110	1290	1470	1650	1830	2010
10 HT	885	1030	1175	1320	1465	1605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.