


# AW 729

<b>TIRE SIZE</b>	<b>480/45 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	134 A8
<b>LI/SS FREE ROLLING</b>	146 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94068975	<b>RC (IN)</b>	99.4
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	34.1	<b>ECE</b>	E11-106R-006798
<b>SLR (IN)</b>	15.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	9240
15 FR	7855
20 FR	7390
25 FR	6600
5 DW	6550
15 DW	5570
20 DW	5240
25 DW	4680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.