

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	160 A8/157 B
<b>LI/SS FREE ROLLING</b>	172 A6/169 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1354	<b>ECE</b>	E11-106R-004556
<b>SLR (MM)</b>	581	<b>PR</b>	18
<b>RC (MM)</b>	4017		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.70	2.80	2.90
10 FR	8455	8640	8820
20 FR	7610	7775	7940
30 FR	6765	6910	7055
40 FR	6040	6170	6300
50 FR	5435	5555	5800
10 DW	6040	6175	6300
20 DW	5435	5555	5670
30 DW	4835	4940	5040
40 DW	4315	4410	4500
50 DW	3885	3970	4125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.