


AGRIMAX RT 855

| | |
|---------------------|----------------------------------------------------------------------------------------------------|
| TIRE SIZE | 340/85 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 125 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA-CODE | 94021581 | RC (IN) | 139.4 |
| SW (IN) | 13.9 | RIM REC | W 12 |
| OD (IN) | 46.8 | RIM ALT | W 11 |
| SLR (IN) | 20.9 | ECE | E4-106R-000604 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------|------|------|------|------|------|------|
| 30 | 2010 | 2340 | 2660 | 2990 | 3320 | 3640 |
| 25 | 2010 | 2340 | 2660 | 2990 | 3320 | 3640 |
| 20 | 2150 | 2500 | 2850 | 3210 | 3560 | 3900 |
| 5 LT | 2690 | 3130 | 3570 | 4010 | 4450 | 4880 |
| 5 HT | 2150 | 2500 | 2850 | 3210 | 3560 | 3900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.