

AGRIMAX SPARGO SB

TIRE SIZE	VF 270/95 R 48
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR / PULVERIZADOR AGRÍCOLA
VERSÃO	STEEL BELTED
TIRE TYPE	TL
LI/SS	155 D



DIMENSÕES IS STANDARD

SW (MM)	280	RIM REC	W9
OD (MM)	1745	ECE	E11-106R-0010463
SLR (MM)	815	SRI	825
RC (MM)	5373		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1660	1875	2085	2260	2510	2650	2895	3145	3355	3530
FROM 65 TO 40	1825	2055	2290	2480	2755	2910	3180	3450	3685	3875
30	1860	2100	2335	2535	2810	2970	3245	3520	3760	3955
20	1895	2140	2380	2580	2865	3025	3305	3590	3830	4030
10	2005	2265	2520	2730	3030	3200	3500	3800	4055	4265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.