


AGRIMAX RT 765

| | |
|---------------------|---|
| TIRE SIZE | 710/70 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 173 D ; 176 A8 |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 2061 | RIM ALT | DW 25 B |
| SLR (MM) | 922 | ECE | E4-106R-000807 |
| RC (MM) | 6174 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 3120 | 3640 | 4095 | 4550 | 5005 | 5395 | 5980 | 6500 |
| 50 | 3280 | 3825 | 4300 | 4780 | 5260 | 5665 | 6280 | 6825 |
| 40 | 3410 | 3980 | 4475 | 4970 | 5470 | 5895 | 6535 | 7100 |
| 30 | 3590 | 4190 | 4710 | 5235 | 5760 | 6205 | 6880 | 7475 |
| 10 LT | 4185 | 4880 | 5490 | 6100 | 6710 | 7230 | 8015 | 8710 |
| 10 HT | 3590 | 4190 | 4710 | 5235 | 5760 | 6205 | 6880 | 7475 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.