DATA SHEET

PRINTED ON
22-04-2026

AS 504

TIRE SIZE	**400/70 - 20**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
VERSIÓN	INDUSTRIAL
TIRE TYPE	TL
LI/SS	149 A8

DIMENSIONES IS STANDARD

SW (MM)	408	**RIM REC**	13
OD (MM)	1097	**RIM ALT**	12 SDC; 14; 13 SDC
SLR (MM)	487	**ECE**	E11-106R-004537
RC (MM)	3214	**SRI**	525

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10	4060
25	3445
30	3380
40	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..