

AS 504

TIRE SIZE	16.5/85 - 24
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	155 A8
LI/SS FREE ROLLING	168 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	415	RIM REC	W 13
OD (MM)	1325	RIM ALT	W 14 L; W 15 L
SLR (MM)	584	ECE	E4-106R-001877
RC (MM)	4013	PR	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80
10 FR	7840
25 FR	6665
30 FR	6270
40 FR	5600
10 DW	5425
25 DW	4610
30 DW	4340
40 DW	3875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.