

FLOTATION 648

DIMENSIONI PNEUMATICO	550/60 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/156 B



DIMENSIONI IS STANDARD

SW (MM)	550	RIM REC	AG 16.00
OD (MM)	1240	ECE	E4-106R-002310
SLR (MM)	540	PR	12
RC (MM)	3725		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.80	2.10
10 FR	5175	5755	6300
20 FR	4655	5180	5670
30 FR	4140	4605	5040
40 FR	3695	4110	4500
50 FR	3325	3700	4000
10 DW	3620	4030	4410
20 DW	3255	3630	3970
30 DW	2895	3225	3530
40 DW	2585	2880	3150
50 DW	2325	2590	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.