

AGRIMAX ELOS

| | |
|---------------------|--------------------|
| TIRE SIZE | 480/70 R 34 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 A8 ; 155 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94070299 | RC (IN) | 191.7 |
| SW (IN) | 19.7 | RIM REC | W 15 L |
| OD (IN) | 63.2 | RIM ALT | W 16 L; W 14 L |
| SLR (IN) | 28.9 | ECE | E11-106R-007532 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 30 | 3340 | 3940 | 4530 | 5050 | 5640 | 6150 | 6760 | 7440 | 8040 | 8540 |
| 25 | 3340 | 3940 | 4530 | 5050 | 5640 | 6150 | 6760 | 7440 | 8040 | 8540 |
| 20 | 3570 | 4210 | 4850 | 5400 | 6040 | 6590 | 7230 | 7970 | 8610 | 9150 |
| 5 LT | 4480 | 5270 | 6070 | 6770 | 7560 | 8260 | 9050 | 9960 | 10770 | 11450 |
| 5 HT | 3570 | 4210 | 4850 | 5400 | 6040 | 6590 | 7230 | 7970 | 8610 | 9150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.