


AGRIMAX TERIS

| | |
|---------------------|--|
| TIRE SIZE | 620/75 R 26 CHO |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / COTTON PICKER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 166 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94035809 | RC (IN) | 191.0 |
| SW (IN) | 24.6 | RIM REC | DW 20 B |
| OD (IN) | 62.6 | ECE | E4-106R-001419 |
| SLR (IN) | 28.7 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 |
|---------------|------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5380 | 6190 | 7590 | 8300 | 9120 | 9930 | 10760 | 11680 |
| 25 | 5380 | 6190 | 7590 | 8300 | 9120 | 9930 | 10760 | 11680 |
| 20 | 5760 | 6640 | 8130 | 8880 | 9770 | 10640 | 11520 | 12510 |
| 10 CYC | 8870 | 10220 | 12530 | 13690 | 15050 | 16390 | 17750 | 19280 |
| 5 CYC | 9680 | 11150 | 13680 | 14940 | 16410 | 17880 | 19360 | 21030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.