

# FORESTMAX

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 650/65 R 38                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR / FORESTRY                                                                       |
| VERSION      | STEEL BELTED                                                                             |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 172 A8 ; 186 A2                                                                          |



## DIMENSIONS IS STANDARD

|          |      |         |                  |
|----------|------|---------|------------------|
| SW (MM)  | 645  | RIM REC | DW 20 B          |
| OD (MM)  | 1811 | RIM ALT | DW21B; DW23B     |
| SLR (MM) | 832  | ECE     | E11-106R-0011042 |
| RC (MM)  | 5467 | SRI     | 875              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR          | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  | 3.4  | 3.6   |
|---------------------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| 50                  | 3050 | 3290 | 3520 | 3860 | 4165 | 4370 | 4520 | 4765 | 4930 | 5105 | 5285 | 5500 | 5670  |
| 40                  | 3390 | 3655 | 3910 | 4285 | 4630 | 4855 | 5020 | 5295 | 5475 | 5670 | 5870 | 6115 | 6300  |
| 30                  | 3630 | 3915 | 4190 | 4590 | 4955 | 5195 | 5375 | 5670 | 5865 | 6075 | 6285 | 6545 | 6745  |
| 25                  | 3760 | 4060 | 4345 | 4760 | 5140 | 5390 | 5575 | 5880 | 6080 | 6300 | 6515 | 6790 | 6995  |
| 20                  | 4170 | 4495 | 4810 | 5270 | 5695 | 5970 | 6175 | 6510 | 6735 | 6975 | 7220 | 7520 | 7750  |
| 15                  | 4540 | 4900 | 5245 | 5745 | 6205 | 6505 | 6730 | 7095 | 7340 | 7605 | 7870 | 8195 | 8445  |
| 10                  | 5110 | 5510 | 5900 | 6460 | 6980 | 7315 | 7570 | 7980 | 8260 | 8550 | 8850 | 9215 | 9500  |
| 10 FORESTRY SERVICE | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | 7750  |
| 0 FORESTRY SERVICE  | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | 14490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.