

AGRIMAX RT 765

TIRE SIZE	260/70 R 16
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE / TRAUBENERNTEMASCHINE / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	109 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94021888	RC (IN)	89.9
SW (IN)	10.2	RIM REC	W 8
OD (IN)	30.3	RIM ALT	W 8 L ; W 9 L
SLR (IN)	13.6	ECE	E4-106R-000610

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1070	1230	1410	1600	1770	1960	2120	2270
25	1070	1230	1410	1600	1770	1960	2120	2270
20	1150	1320	1520	1710	1910	2110	2270	2440
5 LT	1430	1650	1900	2140	2380	2620	2830	3040
5 HT	1150	1320	1520	1710	1910	2110	2270	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.